

MATERIAL SAFETY DATA SHEET
物质安全资料表

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION 产品和公司资料

PRODUCT NAME: Anti-ion Migration type PI film based coverlay (SF325C)

产品名称: 耐离子迁移型聚酰亚胺薄膜覆盖膜 (SF325C)

PRODUCT USE: Flexible printed circuit Boards.

用途: 用于挠性印制电路板。

NAME OF COMPANY AND ADDRESS: SHENGYI TECHNOLOGY CO.,LTD.

No.5 Western Industry Road North Industry District,Dongguan SSL
Sci.&Tech.Industry Park,Dongguan City,Guangdong ,P.R.China

公司名称及地址: 广东生益科技股份有限公司;

中国广东省东莞市松山湖科技产业园区北部工业园工业西路5号

FOR MORE INFORMATION CALL:

紧急联络电话: (Monday-Friday, 8:00am-5:00pm)

(0769)22271828(万江)\ 22899388(松山湖)

IN CASE OF EMERGENCY CALL:

(24 Hours/Day, 7 Days/Week)

(0769)22271828(万江)\ 22899388(松山湖)

2. HAZARDS IDENTIFICATION 危害性资料

EMERGENCY OVERVIEW:

紧急情况概述:

A nonflammable, sheet material. Fumes, if decomposed may irritate eyes, nose, and throat.

是一种难燃的片状材料。当分解时产生的气体会刺激眼睛、鼻和咽喉。

POTENTIAL HEALTH HAZARDS:

潜在的危害健康的危险品:

SKIN: Adhesive may cause moderate skin irritation.

皮肤: 胶粘剂可能导致中等程度皮肤过敏。

EYES: Adhesive may cause moderate eye irritation. Fumes may irritate eyes.

眼睛: 胶粘剂可能导致中等程度眼睛过敏。

INHALATION: Trace of chemical solvents may be vapourized and diffused to air in the processes of varnish preparation and coating production.

吸入物: 在涂覆生产过程时,会有少量化学溶剂挥发出来。

INGESTION: Not determined.

摄食: 没有参考值。

3. COMPOSITION/INFORMATION ON INGREDIENTS 组成成份资料

INGREDIENT NAME	CAS #	WEIGHT %
成分名称	化学文摘号	重量比
Polyimide 聚酰亚胺	(25038-81-7)	32-65
Halogen-free adhesive 无卤胶粘剂	Trade secret 商业秘密	35-68

4. FIRST AID MEASURES 首要援助措施

SKIN: Wash in flowing water or shower. Remove contaminated clothing.

皮肤: 脱下已污染衣服,用流动水冲洗。

EYE: Irrigate with flowing water for 15 minutes. If irritation persists, consult a physician.

眼睛: 用流动水冲洗15分钟,如过敏现象持续发生,请求助于医生。

INHALATION: If not breathing, give mouth-to-mouth resuscitation. Call physician.

吸入: 如没有呼吸,请进行人工呼吸。并致电医生。

INGESTION: If large amounts are ingested, consult physician.

摄食: 如吸入大量,请致电医生。

ADVICE TO PHYSICIAN: Treat symptomatically
建议医生: 处理出现的症状。

5. FIRE FIGHTING MEASURES 火灾测试

FLAMMABLE PROPERTIES: N/A
易燃烧性: 不适用
FLASH POINT: N/A
闪点: 不适用
FLASH POINT METHOD: N/A
闪点方式: 不适用
AUTOIGNITION TEMPERATURE: Not determined
自燃点温度: 无规定
UPPER FLAME LIMIT (Volume % in air): N/A
燃烧上限: 不适用
LOWER FLAME LIMIT (Volume % in air): N/A
燃烧下限: 不适用
FLAME PROPAGATION RATE (Solids): UL94 V-0
燃烧等级: UL94 V-0
OSHA FLAMMABILITY CLASS: N/A
OSHA 燃烧级别: 不适用
EXTINGUISHING MEDIA: Water, CO₂ and dry chemical
灭火介质: 水、CO₂及干化学品
SPECIAL FIREFIGHTING PRECAUTIONS/INSTRUCTIONS:
特别火灾指导:
Firemen should wear proper protective equipment and positive pressure self-contained breathing apparatus.
消防员须身穿保护装置及正压呼吸设施。

6. ACCIDENTAL RELEASE MEASURES 意外事故的应变措施

IN CASE OF SPILL OR OTHER RELEASE: (Always wear recommended personal protection equipment)
如有泄漏或其他释放: (通常身穿所推荐的保护设施)
Not applicable, material is an article.
不适用于固体材料。
Spills and releases may have to be reported to local authorities.
有关泄漏应报告当地政府。

7. HANDLING AND STORAGE 仓储指南

NORMAL HANDLING: (Always wear recommended personal protective equipment.)
规范指南: (建议穿戴个人防护设施)
The primary exposure route is inhalation of dust when machine/punched or from fumes or vapors when heated.
主要是预防暴露部位吸入当机器打孔时或冒烟、气化液体受热时所产生的粉尘。
STORAGE RECOMMENDATIONS: N/A
贮存建议: 不适用。

8. EXPOSURE CONTROLS/PERSONAL PROTECTION 泄漏控制/个人防护

ENGINEERING CONTROLS: Use local exhaust ventilation to control dust.
工程控制: 使用当地除尘通风设施。
PERSONAL PROTECTIVE EQUIPMENT:
个人防护措施:
SKIN PROTECTION: For brief contact to material, no precautions other than clean body-covering clothing should needed. Use gloves and aprons when prolonged or frequently repeated contact occurs.

皮肤保护: 对于短暂性的接触材料, 需要时清洗身体或衣服, 无预防措施。对于长期性的接触, 要配带手套和围裙。

EYE PROTECTION: Use appropriate eye protection when machining material.

眼睛保护: 当加工材料时使用眼睛保护装置。

RESPIRATORY PROTECTION: When respiratory protection is required for certain operations, use a NIOSH-approved dust respirator.

呼吸保护: 当进行产生大量粉尘的操作时使用规范的粉尘防毒面罩。

ADDITIONAL RECOMMENDATIONS: N/A

其它建议: 不适用

9. PHYSICAL AND CHEMICAL PROPERTIES 物理化学性能

APPEARANCE: Amber sheets

外观: 琥珀色

PHYSICAL STATE: Solid

物理形态: 固体

ODOR: None, unless heated

气味: 无味, 除非加热

SPECIFIC GRAVITY: (Water = 1.0) 1.4 +/- 0.1

比重: (水= 1.0) 1.4 +/- 0.1

SOLUBILITY IN WATER: (Weight %) Negligible in water

水溶性: (重量%) 在水中可忽略

10. STABILITY AND REACTIVITY 稳定性及反应性

NORMALLY STABLE: (conditions to avoid) Stable

通常稳定: 稳定

INCOMPATIBILITIES: Not determined

不兼容性: 不确定

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂, Oxides of nitrogen if heated in excess of 300 deg. C.

危险的腐化产品: CO, CO₂, NO_x (当加热超过300°C)。

HAZARDOUS POLYMERIZATION? None

危险聚合物: 无

11. TOXICOLOGICAL INFORMATION 毒物学的资料

IMMEDIATE (ACUTE) EFFECTS: Dust may cause moderate eye, skin and respiratory irritation.

敏感反应: 灰尘将导致眼、皮肤中度过敏。

12. ECOLOGICAL INFORMATION 生态学资料

Not Biodegradable

非生物降解。

13. DISPOSAL CONSIDERATIONS 处置问题

Is the unused product a hazardous waste substances list of country hazardous waste if discarded?

No

列入国家危险废物名录的危险废物不能够再利用时是否被丢弃? 不

OTHER DISPOSAL CONSIDERATIONS: Disposal must be made in accordance with all applicable Local regulations.

其它处置问题: 处置必须遵循当地的法律法规。

Suggestion method after products will be discarded:

1. Separate reuse method: crush products into powder, recycling as a filler.

2. Incineration method: incinerate the unused products, this method may produce some organic compound gas.

3. Bury into deep earth.

产品报废之后有以下几种处置方法:

1. 分离法, 将产品粉碎, 可作填充料;
2. 焚烧法, 焚烧过程中可能产生有机化合物气体;
3. 填埋法。

14. TRANSPORT INFORMATION 运输资料

For additional information on shipping regulations affecting this material, contact the information number found on the first page.

附带资料是当运输规则影响到物料时, 请和第一页所提供的联系方式联系。

15. REGULATORY INFORMATION 法规资料

HAZARDOUS WASTE SUBSTANCES LIST OF COUNTRY: 国家危险废物名录

The epoxy resin system components listed in the hazardous waste substances list of country (HW13) .

环氧化合物类被列入国家危险废物名录当中 (HW13)。

ADDITIONAL REGULATORY INFORMATION:

附加法规资料:

SHENGYI TECHNOLOGY CO., LTD does not use polybromide-biphenyls or polybromide-biphenyloxides as a fire retardant in any of our epoxy resin systems.

广东生益科技股份有限公司没有采用多溴联苯或多溴联苯醚作为阻燃剂在产品的环氧树脂体系当中。

16. OTHER INFORMATION 其它资料

ISSUE DATE: 06/04/2016

版本日期: 06/04/2016